

**TL700 TUBELINE LINEAR LED LUMINAIRE**

TL700 Tubeline is a compact linear LED product that features high efficiency LED light source fitted inside a slim round polycarbonate housing. The round profile allows for the product to be orientated at a varying angles which makes the product ideal for display cases, freezer units, retail and counter displays, other concealed lighting applications.

**ELECTRICAL PARAMETERS**

Input Voltage:	24VDC
Power Consumption:	6.5W / 12W / 14.5W
LED Driver Classification:	Constant Voltage
Light Source Classification:	SMD2835
Power Connection:	2.5mm DC Plug

**MECHANICAL SPECIFICATIONS**

Minimum IK Rating:	IK10
IP Protection Rating:	IP54
Nominal Lengths:	600mm / 1200mm / 1500mm
Construction Material:	Toughened Polycarbonate
Fixing Method:	Round Mounting Clip
Recommended Ambient Temp:	-25°C - 60°C

**CONFIGURATION OPTIONS**

- 900mm length available by request
- Other non standard lengths available by special request
- Dimmable LED driver configurations by request

**PHOTOMETRIC INFORMATION**

Typical Lumen Efficacy:	90lm/W
CCT Colour Temperature:	3000K / 4000K / 6500K
Colour Rendering (Ra):	>85Ra
Beam Angle/Viewing Angle:	120°

**CONTROL OPTIONS**

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**CASAMBI****COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	<b>TL700</b>
Specify LED CCT:	<b>3000K / 4000K / 6500K</b>
Specify Length:	<b>600mm / 1200mm / 1500mm</b>
Specify Wattage:	<b>6.5W / 12W / 14.5W</b>
Included Accessory:	<b>Stainless Steel Mounting Clips</b>
Control Option:	<b>Non Dimmable / DALI / Casambi / DMX</b>

All product details are subject to change without notice. Final specifications may vary.

