

TR20124 LED TRACK LIGHT

TR20124 is a professional LED track mounted spotlight with integrated LED light source and specular aluminium reflector. TR20124 is available in a variety of beam angles, colour options and other configurations. Applications include museums, galleries, retail environments, residential developments, other commercial and residential projects.

ELECTRICAL PARAMETERS

Input Voltage:	220-240VAC
Power Consumption:	24W
LED Driver Classification:	Integral Constant Current
Light Source Classification:	CREE COB

MECHANICAL SPECIFICATIONS

IP Protection Rating:	IP20
Body Dimensions:	2 x 59.5x138mm
Track Adaptor:	Single-Circuit / Three Circuit
Construction Material:	Extruded Aluminum
Standard Colour/Finish:	Black / White
Recommended Ambient Temp:	15°C - 45°C



CONFIGURATION OPTIONS

- Surface mounted version also available
- Non standard colours available by special request
- Integral phase dimmable LED driver available by request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	110lm/W
CCT Colour Temperature:	3000K / 4000K / 5000K
Colour Rendering (Ra):	>80Ra
Beam Angle/Viewing Angle:	10° / 24° / 38° / 20° / 60°

CONTROL OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.



COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70



CASAMBI

ORDERING INFORMATION

Model Number:	TR20124
Specify LED CCT:	3000K / 4000K / 5000K
Specify Beam Angle:	10° / 24° / 38° / 20° / 60°
Specify Finish/Colour:	White / Black
Dimming Configuration	Non-Dim / Phase Dimmable / DALI
Track Adaptor Option:	Single-Circuit / Three Circuit
Optional Base:	Surface Mounted Base By Request



All product details are subject to change without notice. Final specifications may vary.