

TREK 60 LINEAR LIGHTING SYSTEM

Trek 60 is a modern LED luminaire that integrates onto conventional three-circuit track systems. The product is built with high grade materials and is available with powerful LED output configurations. Trek 60 can be used for museums, galleries, retail spaces, industrial lighting, and other commercial projects.

ELECTRICAL PARAMETERS

Input Voltage:	200-240VAC / 110-277VAC
Power Consumption:	30W / 40W / 60W
LED Driver Classification:	Integral Constant Current
Light Source Classification:	Epistar SMD

MECHANICAL SPECIFICATIONS

IP Protection Rating:	IP40
Luminaire Profile Dimensions:	60(W) x 86mm(H)
Luminaire Nominal Length:	343mm / 363mm / 493mm
Construction Material:	Aluminium
Standard Colour/Finish:	Powdercoated
Recommended Ambient Temp:	-40°C - 50°C



CONFIGURATION OPTIONS

- Can design and supply complete three-circuit track systems
- Special colour finishes available by request
- Integral DALI dimmable LED driver available by request
- Custom light distribution configurations available

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	140lm/W
CCT Colour Temperatures:	3000K / 4000K / 5000K
Colour Rendering (Ra):	>85Ra
UGR Glare rating:	<19 UGR

CONTROL OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.



COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70



CASAMBI

ORDERING INFORMATION

Model Number:	Trek-60 (TRK60)
Specify LED CCT:	3000K / 4000K / 5000K
Specify Beam Angle:	22° / 45° / 90°
Specify Finish/Colour:	Black / White / Silver
Wattage Configuration:	30W / 40W / 60W
Light Distribution Mode:	Symmetrical / Asymmetrical

All product details are subject to change without notice. Final specifications may vary.



toll-free: 1300 295 367

email: mail@industrialight.com.au

sales reps:



mobile: 0488 839 917



mobile: 0488 844 503

