

## KINNECT TXR LINEAR INDUSTRIAL SYSTEM

Kinnect TXR is an industrial grade lighting solution for linear installation. The system consists of a continuous trunking profile which accepts quick connect luminaires of different configurations. The design provides for a sleek and seamless installation. Kinnect TXR is ideal for processing facilities, manufacturing, warehouses, supermarkets, galleries, and other industrial projects.

### ELECTRICAL PARAMETERS

Input Voltage:	100-240VAC
Power Consumption:	18W / 25W / 35W / 40W / 60W
LED Driver Classification:	Constant Current
Light Source Classification:	SMD3030 Modular

### MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IK10	
IP Protection Rating:	IP20	
Nominal Luminaire Lengths:	580mm / 1160mm / 1450mm	
Construction Material:	Extruded Aluminum	
Standard Colour/Finish:	White / Black	
Recommended Ambient Temp:	-40°C - 50°C	

### CONFIGURATION OPTIONS

- 2HR Emergency Module Available
- Modular Trunking Options inc Track Spot Module
- Integral DALI dimmable LED driver available by request

### PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	130lm/w
CCT Colour Temperature:	3000K / 400K / 6500K
Colour Rendering (Ra):	>85Ra
Beam Angle/Viewing Angle:	20° / 60° / 90°



### CONFIGURATION OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

### COMPLIANCE & CERTIFICATION



- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

### ORDERING INFORMATION

Model Number:	<b>Kinnect TXR-</b>
Specify LED CCT:	<b>3000K / 4000K / 6500K</b>
Specify Beam Angle:	<b>20° / 60° / 90° / Asymmetrical / Dual Assym</b>
Luminaire Length:	<b>580mm / 1160mm / 1450mm</b>
Trunking Lengths:	<b>Customised Lengths Available</b>
Dimming Option:	<b>DALI / 2HR EMERG / TRACK-SPOT</b>

All product details are subject to change without notice. Final specifications may vary.

