


VCP300 SURFACE MOUNT LED CEILING LUMINAIRE

VCP300 is an industrial grade ceiling mounted luminaire that is suitable for general area lighting. The slimline fittings are constructed from powdercoated steel body with polycarbonate lens. VCP300 features integral LED light source and LED driver. Applications include cool rooms, ceiling/canopy lighting, commercial, projects, industrial projects.

ELECTRICAL PARAMETERS

Input Voltage:	120-277VAC
Power Consumption:	40W
LED Driver Classification:	Integral Constant Current
Light Source Classification:	Citizen/ COB

MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IK10	
IP Protection Rating:	IP65	
Fitting Recessed Depth:	268x115mm	
Construction Material:	Aluminium Alloy	
Standard Colour/Finish:	UV Stabilised / Powdercoated	
Recommended Ambient Temp:	-40°C - 50°C	

CONFIGURATION OPTIONS

- Non standard colours available by special request
- Integral DALI dimmable LED driver available by request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	85lm/W
CCT Colour Temperature:	3000K / 4000K / 6000K
Colour Rendering (Ra):	>80Ra
Beam Angle/Viewing Angle:	120°

CONTROL OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**CASAMBI****COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	VCP300
Specify LED CCT:	3000K / 4000K / 6000K
Specify Wattage:	40W
Specify Finish/Colour:	Dark Bronze / Black / White
Input Voltage Option:	120-277VAC / 24VDC
Control Option:	Non-Dimmable / DALI / Phase Dim



All product details are subject to change without notice. Final specifications may vary.