

VNP POLYCARBONATE SLIM/LOW-PROFILE LED LUMINAIRE

VNP is a low profile LED LUMINAIRE that is constructed from fire-resistant polycarbonate. The luminaires are available in several different size configurations and are ideal for installation into modern commercial environments including offices, storerooms, workshops, schools, retail showrooms etc.

ELECTRICAL PARAMETERS

Input Voltage:	100-240VAC
Power Consumption:	20/24/30/40/48/60/80W
LED Driver Classification:	Integral, Constant Current
Light Source Classification:	Industrialight SMD2835 LED

MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IK08
IP Protection Rating:	IP20
Profile Dimensions:	125x40mm
Construction Material:	Toughened Polycarbonate
Standard Colour/Finish:	White
Recommended Ambient Temp:	-15°C - 55°C



CONFIGURATION OPTIONS

- Surface mounted slimline series
- 24VDC version available by special request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	110lm/W
CCT Colour Temperature:	3000K/4000K/5000K/6500K
Colour Rendering (Ra):	>90Ra
Beam Angle/Viewing Angle:	120°

CONTROL OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

COMPLIANCE & CERTIFICATION



- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70



ORDERING INFORMATION

Model Number:	VNP Slim Profile Series
Specify LED CCT:	3000K/4000K/5000K/6500K
Nominal Length:	640/880/1030/1314/1620/1920/2488mm
Specify Wattage:	20/24/30/40/48/60/80W
Input Voltage Option:	100-240VAC / 24VDC
Control Option:	Non-Dimmable / DALI / Phase Dim



All product details are subject to change without notice. Final specifications may vary.