

## VPB SLIMLINE LED BATTEN LUMINAIRE

VPB is a slimline linear LED LUMINAIRE which is an ideal replacement for slimline fluorescent style fittings and other traditional light fittings. VPB is a discrete slimline design and delivers excellent illumination performance. The luminaires are available in 300mm, 600mm, 900mm, 1200mm length variants.

### ELECTRICAL PARAMETERS

Input Voltage:	100-240VAC
Power Consumption:	39W
LED Driver Classification:	Integral, Constant Current
Light Source Classification:	SMD2835 LED



### MECHANICAL SPECIFICATIONS

IK Rating:	IK10
IP Protection Rating:	IP20
Dimensions:	1200x80x35mm
Construction Material:	Aluminium & Polycarbonate
Diffuser Material:	Polycarbonate
Fixing Method:	Direct Mounting
Recommended Ambient Temp:	-30°C - 50°C

### CONFIGURATION OPTIONS

- Customised lengths available by special request
- Optional 24VDC version available by special request
- External dimmable LED driver available by special request

### PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	100lm/W
CCT Colour Temperature:	3000K/4000K/6500K
Colour Rendering (Ra):	>80Ra
Beam Angle/Viewing Angle:	120°



### CONTROL OPTIONS

LED output colour temperature (CCT) is user-selectable using the on-board switch control panel. Other dimming and control options are available by special request, including DALI, Casambi, Wireless, 1-10V, analogue dimming.



### COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70



### ORDERING INFORMATION

Model Number:	<b>VPB1200</b>
LED CCT:	<b>3000K/4000K/6000K (Selectable)</b>
Specify Beam Angle:	<b>120°</b>
Colour:	<b>White / White Opal</b>
Nominal Length:	<b>600mm / 1200mm / Custom</b>
Input Voltage Option:	<b>100-240VAC or 12VDC</b>
Control Option:	<b>Non Dimmable / DALI / Casambi / 1-10V</b>

All product details are subject to change without notice. Final specifications may vary.

