

VTN DIFFUSED POLYCARBONATE BATTEN LUMINAIRE

VTN is a diffused integrated LED batten luminaire that is constructed from fire-resistant polycarbonate body and diffuser. VTN luminaires are an ideal replacement for existing fluorescent diffused light fittings and they are best suited for modern commercial environments including offices, storerooms, workshops, garages, schools, work spaces, retail showrooms etc.

ELECTRICAL PARAMETERS

Input Voltage:	100-240VAC
Power Consumption:	10W/12W/15W/20W/24W
LED Driver Classification:	Integral, Constant Current
Light Source Classification:	Industrialight SMD2835 LED

MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IK08
IP Protection Rating:	IP20
Nominal Luminaire Lengths:	640/758/908/1192/1575mm
Construction Material:	Toughened Polycarbonate
Standard Colour/Finish:	White
Recommended Ambient Temp:	-15°C - 55°C



CONFIGURATION OPTIONS

- AS2293 Emergency Version Available
- Surface mounted LED batten
- 24VDC version available by special request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	110lm/W
CCT Colour Temperature:	3000K/4000K/5000K/6500K
Colour Rendering (Ra):	>90Ra
Beam Angle/Viewing Angle:	120°

CONTROL OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.



COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70



ORDERING INFORMATION

Model Number:	VTN
Specify LED CCT:	3000K/4000K/5000K/6500K
Nominal Luminaire Length:	640/758/908/1192/1575mm
Specify Wattage:	10W/12W/15W/20W/24W
Emergency Version:	2HR Emergency AS2293
Control Option:	Non-Dimmable / DALI / Phase Dim

All product details are subject to change without notice. Final specifications may vary.

