

VWP180 SURFACE MOUNTED WALL LUMINAIRE

Industralight VWP180 Wall Luminaire is a triangular, exterior wall lighting fixture designed for commercial projects. Its innovative shape adds a modern touch, while its robust construction ensures durability and reliability, offering both style and functionality for any commercial exterior lighting needs.

Ideal for facade illumination, landscape accenting, architectural highlighting, and pathway lighting, the Industralight VWM Wall Luminaire enhances visual appeal and safety in commercial environments.

SPECIFICATIONS

Model Variant:	VWP180
Input Voltage:	220-240VAC
Max Power Consumption:	22W
Trim Dimensions:	180x180mm
Overall Depth:	180mm
LED Classification:	COB
Fixture Material:	Aluminium
Typical Light Source Efficacy:	90lm/W
Beam Angle Options:	8° / 15° / 50°
Asymmetrical Variant	70°x 20°
LED Driver Power Factor:	>0.9
Recommended Ambient Temp:	-20 ~ +45° C
IP Protection Rating:	IP65

PHOTOMETRIC INFORMATION

VWP180-2700K	CCT: 2700K
VWP180-3000K	CCT: 3000K
VWP180-4000K	CCT: 4000K
VWP180-5700K	CCT: 5700K



Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Security lighting, indirect area lighting, courtyards, common areas, facade illumination and architectural highlighting, enhancing the aesthetic appeal of commercial exteriors. It also serves effectively for landscape accenting and pathway lighting, ensuring safety and navigability in commercial settings.

CONTROL & DIMMING COMPATIBILITY

VWP180 is typically supplied in non dimmable configuration. Optional dimmable LED Drivers by special request, dimming options include phase dimmable, 1-10V, DALI or special control inc CCT tunable.

ORDERING INFORMATION

VWP180SV-2700K	Surface Mounted Wall Luminaire 22W Silver 2700K
VWP180SV-3000K	Surface Mounted Wall Luminaire 22W Silver 3000K
VWP180SV-4000K	Surface Mounted Wall Luminaire 22W Silver 4000K
VWP180BK-2700K	Surface Mounted Wall Luminaire 22W Black 2700K
VWP180BK-3000K	Surface Mounted Wall Luminaire 22W Black 3000K
VWP180BK-4000K	Surface Mounted Wall Luminaire 22W Black 4000K

CONFIGURATION OPTIONS



- Surface can be refinished as required
- Optional Low Glare Baffle (fitted by special request)
- Specify lens beam angle 8° / 15° / 50° or Assym Forward Throw
- **Custom options may be subject to minimum quantities

All product specifications are subject to change without notice. Industralight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.

