

VWP200 WEDGE LED LUMINAIRE

VWP200 is contemporary wall mounted luminaire which can be used in up or down configuration. The fitting features a toughened design making it suitable for demanding commercial and industrial projects. Typical applications include building perimeters, security lighting, retail and shopping complexes, courtyards, area lighting, task lighting, mining, industrial and commercial projects.



ELECTRICAL PARAMETERS

Input Voltage:	120-277VAC
Power Consumption:	14W / 20W / 28W / 52W
LED Driver Classification:	Integral Constant Current LED Driver
Light Source Classification:	Citizen COB

MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IK10
IP Protection Rating:	IP65
Nominal Dimensions:	158x141x107mm
Construction Material:	Powdercoated Aluminium
Standard Colour/Finish:	Black
Recommended Ambient Temp:	-10 ~ +50°C
Net Weight:	3.0KG



CONFIGURATION OPTIONS

- 135x85° Asymmetrical optical configuration by request
- Non standard fitting colours available by special request
- Higher power 52W configuration available by special request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	95lm/W
CCT Colour Temperature:	3000K / 4000K / 6500K
Colour Rendering (Ra):	>80Ra
Beam Angle/Viewing Angle:	100°



CONTROL OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.



COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70



ORDERING INFORMATION

Model Number:	VWP200
Specify LED CCT:	3000K / 4000K / 6500K
Specify Beam Angle:	100° / 135x85°
Specify Finish/Colour:	Black / Silver
Specify Wattage:	14W / 20W / 28W / 52W
Control Option:	Non-Dimmable / DALI / Phase Dim

All product details are subject to change without notice. Final specifications may vary.

