


W3345 IP65 LED WALL LUMINAIRE

W3345 is a commercial grade wall light with solid extruded body, and powdercoated. Corrosion resistant marine grade finish makes the product good for use in all exterior locations. Tempered glass visor and integrated LED control gear. Available in up and down or down only variants with various other custom lighting options.

ELECTRICAL PARAMETERS

| | | |
|------------------------------|---------------------|---|
| Input Voltage: | 220-240VAC |  |
| Power Consumption: | 16W | |
| LED Driver Classification: | AC LED Driver | |
| Light Source Classification: | Epistar SMD2835 LED | |


MECHANICAL SPECIFICATIONS


| | | |
|-------------------------------|---------------------------------|---|
| Minimum IK Rating: | IK10 |  |
| IP Protection Rating: | IP65 | |
| Dimensions: | 220x70x45mm | |
| Body Height: | 45mm | |
| Overall Projection From Wall: | 70mm | |
| Construction Material: | Aluminium | |
| Standard Colour/Finish: | Black / White / Silver / Custom | |
| Recommended Ambient Temp: | -15°C - 55°C | |

CONFIGURATION OPTIONS

- Non standard colours available by special request
- Remote mounted DALI dimmable LED driver available

PHOTOMETRIC INFORMATION

| | | |
|---------------------------|------------------------------|---|
| Typical Lumen Efficacy: | 85lm/W |  |
| CCT Colour Temperature: | 3000K / 4000K / 6000K / RGBW | |
| Colour Rendering (Ra): | >85Ra | |
| Beam Angle/Viewing Angle: | 100° / 2x100° | |

**CONTROL OPTIONS**

W3345 can be customised or configured by request. Up and down or down only options. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

| | |
|-------------------------|--------------------------------------|
| Model Number: | W3345 |
| LED Power: | 16W |
| Specify LED CCT: | 3000K / 4000K / 6000K / RGBW |
| Specify Configuration:: | Down Only / Up and Down |
| Specify Finish/Colour: | Black / White / Custom |
| Input Voltage Option: | 240VAC / 24VDC |
| Dimmable Option: | Non Dimmable / DALI / Casambi |

All product details are subject to change without notice. Final specifications may vary.

