

W7275 IP65 LED WALL MOUNTED LUMINAIRE


W7275 wall luminaire is a classically designed LED product constructed from aluminium with polycarbonate. Highly corrosion resistant with powdercoated surface. Suitable for indoor and outdoor lighting applications in commercial and domestic projects. Features stable SMD integrated LED and LED Driver

ELECTRICAL PARAMETERS

Input Voltage:	220-240VAC
Power Consumption:	8W
LED Driver Classification:	Constant Current
Light Source Classification:	Epistar SMD LED

**MECHANICAL SPECIFICATIONS**

Minimum IK Rating:	IK10
IP Protection Rating:	IP65
Overall Height:	90mm
Dimensions:	275x90x85mm
Overall Projection From Wall:	85mm
Construction Material:	Aluminium & Polycarbonate
Standard Colour/Finish:	Black / White / Silver / Custom
Recommended Ambient Temp:	-15°C - 55°C

**CONFIGURATION OPTIONS**

- Non standard colours available by special request
- Remote mounted DALI LED driver available

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	100lm/w
CCT Colour Temperature:	3000K / 4000K / 6000K / RGBW
Colour Rendering (Ra):	>85Ra
Beam Angle/Viewing Angle:	10° / 30° / 60°

**CONTROL OPTIONS**

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	W7275
Specify LED CCT:	3000K / 4000K / 6000K / RGBW
Specify Beam Angle:	10° / 30° / 60°
Specify Finish/Colour:	Black / White / Custom
Input Voltage Option:	240VAC / 12VDC / 24VDC
Dimmable Option:	Non Dimmable / DALI / Casambi

All product details are subject to change without notice. Final specifications may vary.

