

WDL204 EXTERIOR WALL LUMINAIRE - IP65

WDL204 is a high-performance commercial LED wall light designed for exterior applications. For commercial lighting projects, WDL series enhances building facades, columns, and architectural elements with a modern touch. Built for durability, it delivers efficient illumination while complementing contemporary exteriors. Ideal for commercial spaces seeking both functionality and aesthetic appeal.

ELECTRICAL PARAMETERS

Input Voltage:	100-240VAC
Power Consumption:	20W / 25W / 30W
LED Driver Classification:	Integral Constant Current
Lamp Configuration:	CREE CXA COB

MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IK10	 
IP Protection Rating:	IP65	
Profile Dimensions:	125mm Dia x 204mm (height)	
Construction Material:	Aluminium with Glass Visor	
Standard Colour/Finish:	Black / White / Silver / Custom	
Recommended Ambient Temp:	-20°C - 45°C	

CONFIGURATION OPTIONS

- Also available in up & down only version by request (WDL245)
- Non-standard colours available by special request
- DALI dimmable configuration by request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	105lm/W
CCT Colour Temperature:	3000K / 4000K / 5000K
Colour Rendering (Ra):	>85Ra
Beam Angle/Viewing Angle:	1 x 12° / 1 x 36°

CONTROL OPTIONS

WDL204 can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

COMPLIANCE & CERTIFICATION**CASAMBI**

- IESNA2002 RCM
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	WDL204
Specify LED Lamp Option:	3000K / 4000K / 6000K
Optional Lens Beam Angle:	12° / 36°
Specify Finish/Colour:	Black / White / Matt Silver / Custom
Input Voltage Option:	100-240VAC
Specify Wattage:	20W / 25W / 30W
Dimming Option:	Non Dimmable / Phase Dimmable
Configuration:	Down Only

All product details are subject to change without notice. Final specifications may vary.



