

**WDL273 EXTERIOR WALL LUMINAIRE - IP65**

WDL273 is a high-performance commercial LED wall light designed for exterior applications. Featuring an up-and-down lighting design, it enhances building facades, columns, and architectural elements with a modern touch. Built for durability, it delivers efficient illumination while complementing contemporary exteriors. Ideal for commercial spaces seeking both functionality and aesthetic appeal.

**ELECTRICAL PARAMETERS**

|                            |                           |
|----------------------------|---------------------------|
| Input Voltage:             | 100-240VAC                |
| Power Consumption:         | 28W / 36W / 58W           |
| LED Driver Classification: | Integral Constant Current |
| Lamp Configuration:        | CREE CXA COB              |

**MECHANICAL SPECIFICATIONS**

|                           |                                 |                                                                                   |                                                                                   |
|---------------------------|---------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|
| Minimum IK Rating:        | IK10                            |  |  |
| IP Protection Rating:     | IP65                            |                                                                                   |                                                                                   |
| Profile Dimensions:       | 160mm Dia x 273mm (height)      |                                                                                   |                                                                                   |
| Construction Material:    | Aluminium with Glass Visor      |                                                                                   |                                                                                   |
| Standard Colour/Finish:   | Black / White / Silver / Custom |                                                                                   |                                                                                   |
| Recommended Ambient Temp: | -20°C - 45°C                    |                                                                                   |                                                                                   |

**CONFIGURATION OPTIONS**

- Also available in down only version by request (WDL224)
- Non-standard colours available by special request
- DALI dimmable configuration by request

**PHOTOMETRIC INFORMATION**

|                           |                       |
|---------------------------|-----------------------|
| Typical Lumen Efficacy:   | 105lm/W               |
| CCT Colour Temperature:   | 3000K / 4000K / 5000K |
| Colour Rendering (Ra):    | >85Ra                 |
| Beam Angle/Viewing Angle: | 2 x 12° / 2 x 36°     |

**CONTROL OPTIONS**

WDL273 can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**COMPLIANCE & CERTIFICATION****CASAMBI**

- IESNA2002 RCM
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

|                           |                                             |
|---------------------------|---------------------------------------------|
| Model Number:             | <b>WDL273</b>                               |
| Specify LED Lamp Option:  | <b>3000K / 4000K / 6000K</b>                |
| Optional Lens Beam Angle: | <b>2 x 12° / 2 x 36°</b>                    |
| Specify Finish/Colour:    | <b>Black / White / Matt Silver / Custom</b> |
| Input Voltage Option:     | <b>100-240VAC</b>                           |
| Specify Wattage:          | <b>2x14W / 2x18W / 2x29W</b>                |
| Dimming Option:           | <b>Non Dimmable / Phase Dimmable</b>        |
| Configuration:            | <b>Up &amp; Down (Direct-Indirect)</b>      |

All product details are subject to change without notice. Final specifications may vary.

toll-free: **1300 295 367**email: **mail@industrialight.com.au**

sales reps:

mobile: **0488 839 917**mobile: **0488 844 503**

## WDL273 UP & DOWN VERSION

