

**WPK575 LED WALL PACK LUMINAIRE**

WPK575 is a professional wall mounted luminaire for commercial and industrial projects. The body is manufactured from toughened materials with vandal resistant polycarbonate visor. WPK575 is ideal for general purpose lighting in courtyards, common areas, carparks, security lighting, commercial sites.

**ELECTRICAL PARAMETERS**

Input Voltage:	100-277VAC
Power Consumption:	45W / 70W / 100W / 150W
LED Driver Classification:	Integral High Efficiency
Light Source Classification:	Lumileds

**MECHANICAL SPECIFICATIONS**

Minimum IK Rating:	IK10
IP Protection Rating:	IP65
Nominal Dimensions:	370x230mm
Overall Depth From Wall:	198mm
Construction Material:	Aluminium & Polycarbonate
Standard Colour/Finish:	Black
Recommended Ambient Temp:	-30°C - 45°C

**CONFIGURATION OPTIONS**

- Optional 200-480VAC version by special request
- DALI dimmable LED driver available by request

**PHOTOMETRIC INFORMATION**

Typical Lumen Efficacy:	110lm/W
CCT Colour Temperature:	3000K / 4000K / 6500K
Colour Rendering (Ra):	>80Ra
Beam Angle/Viewing Angle:	130°

**CONTROL OPTIONS**

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	<b>WPK575</b>
Specify LED CCT:	<b>3000K / 4000K / 6500K</b>
Wattage Configuration:	<b>45W / 70W / 100W / 150W</b>
Finish / Colour:	<b>Black / White / Silver / Custom</b>
Input Voltage Option:	<b>100-277VAC / 24VDC</b>
Control Option:	<b>Non-Dim / DALI / Phase Dim / Casambi</b>



All product details are subject to change without notice. Final specifications may vary.