

WPK620 LED WALL PACK LUMINAIRE

WPK620 is a professional wall mounted luminaire for commercial and industrial projects. The body is manufactured from toughened materials with vandal resistant polycarbonate visor. WPK620 is ideal for general purpose lighting in courtyards, common areas, carparks, security lighting, commercial sites.

ELECTRICAL PARAMETERS

Input Voltage:	100-277VAC
Power Consumption:	35W / 50W / 70W / 100W
LED Driver Classification:	Integral High Efficiency
Light Source Classification:	Lumileds

MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IK10
IP Protection Rating:	IP65
Nominal Dimensions:	269x265mm
Overall Depth From Wall:	196mm
Construction Material:	Aluminium & Polycarbonate
Standard Colour/Finish:	Black
Recommended Ambient Temp:	-30°C - 45°C

**CONFIGURATION OPTIONS**

- Optional 200-480VAC version by special request
- DALI dimmable LED driver available by request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	110lm/W
CCT Colour Temperature:	3000K / 4000K / 6500K
Colour Rendering (Ra):	>80Ra
Beam Angle/Viewing Angle:	130°

**CONTROL OPTIONS**

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	WPK620
Specify LED CCT:	3000K / 4000K / 6500K
Wattage Configuration:	35W / 50W / 70W / 100W
Finish / Colour:	Black / White / Silver / Custom
Input Voltage Option:	100-277VAC / 24VDC
Control Option:	Non-Dim / DALI / Phase Dim / Casambi



All product details are subject to change without notice. Final specifications may vary.