

**WPL300G ARCHITECTURAL LED WALL PACK**

WPL300G is an industrial wall luminaire which is designed for use in commercial and industrial projects. The product features a robust housing, high quality LED components, and can be supplied with a variety of optic configurations. Is ideal for carpark lighting, security area lighting, building perimeter lighting, special industrial projects, government and infrastructure sites, other commercial locations.

**ELECTRICAL PARAMETERS**

Input Voltage:	120-240VAC
Power Consumption:	40W
LED Driver Classification:	Integral Constant Current LED Driver
Light Source Classification:	CREE XP-E/T

**MECHANICAL SPECIFICATIONS**

Minimum IK Rating:	IK10			
IP Protection Rating:	IP65			
Dimensions:	158x353mm			
Body Construction:	Die Cast Aluminium Body			
Lens Material:	Toughened Polycarbonate			
Standard Colour/Finish:	Dark Bronze			
Recommended Ambient Temp:	-15 ~ +50°C			

**CONFIGURATION OPTIONS**

- Various Optical Lens Configurations Available
- Non standard fitting colours available by special request
- Custom dimmable solutions available by special request

**PHOTOMETRIC INFORMATION**

Typical Lumen Efficacy:	80lm/W
CCT Colour Temperature:	3000K / 4000K / 5000K
Colour Rendering (Ra):	>80Ra
Beam Angle/Viewing Angle:	120°

**CONTROL OPTIONS**

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**COMPLIANCE & CERTIFICATION****CASAMBI**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	<b>WPL300G</b>
Specify LED CCT:	<b>3000K / 4000K / 5000K</b>
Specify Optic Config:	<b>120° / 135x120° / Type II / Type III IES</b>
Specify Finish/Colour:	<b>Dark Bronze</b>
Specify Wattage:	<b>40W</b>
Control Option:	<b>Non-Dimmable / DALI / Phase Dim</b>

All product details are subject to change without notice. Final specifications may vary.

