

**WPL50G ARCHITECTURAL LED WALL PACK**

WPL50G is an industrial quality LED wall pack luminaire. The product features a robust housing with high quality integrated LED light source and LED driver. WPL50G is a versatile product option and can be used for a variety of commercial applications such as security lighting, perimeter lighting, passageways, pathways, stairwells, commercial exterior and interior projects.

**ELECTRICAL PARAMETERS**

Input Voltage:	120-240VAC
Power Consumption:	14W
LED Driver Classification:	Integral Constant Current LED Driver
Light Source Classification:	CREE XP-E/T

**MECHANICAL SPECIFICATIONS**

Minimum IK Rating:	IK10
IP Protection Rating:	IP65
Dimensions:	165x165x180mm
Body Construction:	Die Cast Aluminium Body
Lens Material:	Toughened Polycarbonate
Standard Colour/Finish:	Dark Bronze
Recommended Ambient Temp:	-15 ~ +50°C

**CONFIGURATION OPTIONS**

- Non standard fitting colours available by special request
- Custom dimmable solutions available by special request

**PHOTOMETRIC INFORMATION**

Typical Lumen Efficacy:	80lm/W
CCT Colour Temperature:	3000K / 4000K / 6500K
Colour Rendering (Ra):	>80Ra
Beam Angle/Viewing Angle:	90°

**CONTROL OPTIONS**

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	<b>WPL50G</b>
Specify LED CCT:	<b>3000K / 4000K / 6500K</b>
Specify Wattage:	<b>14W</b>
Finish / Colour:	<b>Dark Bronze / White / Silver / Custom</b>
Input Voltage Option:	<b>100-277VAC / 24VDC</b>
Control Option:	<b>Non-Dim / DALI / Phase Dim / Casambi</b>

All product details are subject to change without notice. Final specifications may vary.

