

X5 ROUND LED PANEL LUMINAIRE

Industrialight X5 is a specially design for high-end interiors, offices, hotels, retail, and other commercial projects. X5 incorporates advanced light guide technology and high brightness micro-SMD LED light source to deliver a smooth and uniform light fixture. Various sizes between 300mm to 1200mm in diameter are available with custom options available by special request.

ELECTRICAL PARAMETERS

Input Voltage:	100-265VAC
Power Consumption:	Various up to 110W
LED Driver Classification:	Remote Mounted Constant Current
Light Source Classification:	Micro SMD LED

MECHANICAL SPECIFICATIONS

Minimum IK Rating:	IK08	
IP Protection Rating:	IP44	
Nominal Diameters:	Various Sizes 300mm – 1200mm	
Panel Thickness:	9mm	
Construction Material:	Aluminium + Polycarbonate	
Standard Colour/Finish:	White Trim / Silver Trim	
Installation Method:	Wire Suspension / Recessed	
Recommended Ambient Temp:	-15°C - 45°C	

CONFIGURATION OPTIONS

- Non standard sizes available by special request
- 1-10V dimmable LED driver available by request
- DALI dimmable LED driver available by request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	90lm/W
CCT Colour Temperature:	3000K / 4000K / 5000K
Colour Rendering (Ra):	>90Ra
Beam Angle/Viewing Angle:	120°



CONTROL OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.



COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

ORDERING INFORMATION

Model Number:	X5 / R
Specify LED CCT:	3000K / 4000K / 5000K
Specify Diameter:	300mm / 600mm / 900mm / 1200mm
Specify Wattage:	14W / 28W / 32W / 48W / 72W / 90W
Mounting Option:	Wire Suspension / Ceiling Recessed
Custom Size:	Specify Custom Size / Wattage

All product details are subject to change without notice. Final specifications may vary.

