


## XTR RECESSED SERIES LED PANEL

XTR is a high performance LED lightguide panel with slimline design and excellent lumen performance. The product is manufactured in a variety of sizes and LED configurations. Industrialight XTR panels are designed to be recessed into plaster style ceilings and are supplied complete with ceiling spring clips and remote-mounted LED driver.

### ELECTRICAL PARAMETERS

Input Voltage:	100-240VAC	
Power Consumption:	18-72W	
LED Driver Classification:	Remote Mounted	
Light Source Classification:	Micro SMD LED	

### MECHANICAL SPECIFICATIONS

IP Protection Rating:	IP44	
Nominal Dimensions:	Various Sizes 300mm - 1200mm	
Panel Thickness:	12mm	
Construction Material:	Aero Grade Aluminium + PMMA	
Standard Colour/Finish:	White Trim	
Installation Method:	Plaster Recessed	
Recommended Ambient Temp:	-15°C - 45°C	

### CONFIGURATION OPTIONS

- 1-10V dimmable LED driver available by request
- DALI dimmable LED driver available by request

### PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	100lm/W
Unified Glare rating (UGR):	<19UGR
Colour Rendering (Ra):	>90Ra
Beam Angle/Viewing Angle:	120°



### CONTROL OPTIONS

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.



### COMPLIANCE & CERTIFICATION

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70



### ORDERING INFORMATION

Model Number:	<b>XTR Series</b>
Specify LED CCT:	<b>3000K / 4000K / 5000K / 6500K</b>
Specify Dimensions:	<b>300mm / 600mm / 900mm / 1200mm</b>
Specify Wattage:	<b>18W / 28W / 32W / 48W / 72W / 90W</b>
Dimming Configuration:	<b>Non-Dim / DALI</b>
Installation Type:	<b>Plaster / Gyprock Ceiling</b>

All product details are subject to change without notice. Final specifications may vary.

