

XVT STEEL LINEAR INDUSTRIAL LED LUMINAIRE

XVT is an industrial-grade linear LED light luminaire constructed from stainless steel with toughened lens diffuser. The luminaires are ideal for installation into extreme environments including mining sites, chemical plants, warehouses, factories, underground tunnels, exterior locations etc.

ELECTRICAL PARAMETERS

Input Voltage:	100-240VAC
Power Consumption:	20W / 40W / 48W
LED Driver Classification:	Integral, Constant Current
Light Source Classification:	Industrialight SMD2835 LED

**MECHANICAL SPECIFICATIONS**

Minimum IK Rating:	IK10
IP Protection Rating:	IP66
Nominal Luminaire Lengths:	710mm/1310mm/1610mm
Construction Material:	Stainless Steel
Standard Colour/Finish:	Black / White / Silver
Recommended Ambient Temp:	-20°C - 65°C

CONFIGURATION OPTIONS

- Can be fitted with microwave sensor switch or dimmer
- 24VDC version available by special request

PHOTOMETRIC INFORMATION

Typical Lumen Efficacy:	110lm/W
CCT Colour Temperature:	3000K/4000K/5000K/6500K
Colour Rendering (Ra):	>90Ra
Beam Angle/Viewing Angle:	100°

**CONTROL OPTIONS**

This product can be customised or configured according to the needs of your project. Dimming and control options are available by special request. Control protocols include DALI, Casambi, Wireless, 1-10V, analogue dimming.

**COMPLIANCE & CERTIFICATION**

- IESNA2002
- AS/NZS60598, LM79, LM80
- Lifespan: Exceeds 50,000hrs @ L70

**ORDERING INFORMATION**

Model Number:	XVT Stainless Steel Series
Specify LED CCT:	3000K/4000K/5000K/6500K
Nominal Length:	630mm 1230mm / 1520mm
Specify Wattage:	20W / 40W / 48W
Optional Sensor:	Sensor Switch/Sensor Dimmer
Control Option:	Non-Dimmable / DALI / Phase Dim



All product details are subject to change without notice. Final specifications may vary.